

Remote Control Products Selection Guide

303/433 MHz Remotes	Description	x= Buttons	Relays	Frequency (MHz)	Address Codes (Millions)	Address Selection2	Range ¹ (Feet)	Relay Output ³	Size (Inches) ²	Hi-EMI Motor Noise Tolerant	Momentary, Latched & Toggle Modes	Use With
KTX303Cx	Transmitter, Keyfob Remote	1, 2 or 3		303	16.7	Factory Set	600, 960		2.4x 1.45x 0.5			RCR303C3R
KTX433Cx	Transmitter, Keyfob Remote	1, 2 or 3		433	16.7	Factory Set	600, 960		2.4x 1.45x 0.5			RCR433C3R
KTXW303Cx	Transmitter, Keyfob, Remote, Watertight	3		303	16.7	Factory Set	600, 960		2.6 x 1.91 x 0.7			RCR303C3R
KTXW433Cx	Transmitter, Keyfob, Remote, Watertight	3		433	16.7	Factory Set	600, 960		2.6 x 1.91 x 0.7			RCR433C3R
NTX303Cx	Transmitter, NEMA 4X Polycarbonate Enclosure	1 or 2		303	16.7	Factory Set	600, 960		4.75x 3.2x 3.4			RCR303C3R
NTX433Cx	Transmitter, NEMA 4X Polycarbonate Enclosure	1 or 2		433	16.7	Factory Set	600, 960		4.75x 3.2x 3.4			RCR303C3R
KTXW303C6-x	Transmitter, Handheld Remote	2, 4 or 6		303	16.7	Factory Set	600, 960		3.4x 2.6x 1.0			RCR303C6R
KTXW433C6-x	Transmitter, Handheld Remote	2, 4 or 6		433	16.7	Factory Set	600, 960		3.4x 2.6x 1.0			RCR433C6R
RCR303C3R	Receiver, Remote Control, Learning, 12A Relay Out		3	303	16.7	Learning	600, 960	SPDT, 12A	5.25x 3.5x 1.48		x	
RCR303C6R	Receiver, Remote Control, Learning, 12A Relay Out		6	303	16.7	Learning	600, 960	SPDT, 12A	6.5x 3.85x 1.36		x	

x=1, 2 or 3 channels/buttons

2.4 GHz Remotes	Description	x= Buttons	Relays	Frequency (GHz)	Address Codes (Billions)	Address Selection2	Range ² (Feet)	Relay Output ³	Size (Inches) ²	Hi-EMI Motor Noise Tolerant	Momentary, Latched & Toggle Modes	Use With
KTX245S-x	Transmitter, Keyfob	1, 2 or 3		2.4	4	Factory Set	500		2.4x 1.45x 0.5			RCR245S-3R
KTXW245S3	Transmitter, Keyfob, Watertight			2.4	4	Factory Set	500		2.6 x 1.91 x 0.7			RCR245S-3R
KTXW245S6-x	Transmitter, Handheld, Watertight	1 or 2		2.4	4	Factory Set	500		3.4x 2.6x 1.0			RCR245S-3R
NTX245S-x	Transmitter, NEMA Box	1 or 2		2.4	4	Factory Set	500		4.75x 3.2x 3.4			RCR245S-3R
RCR245S-3R	Receiver, Remote Control, Learning		3	2.4	4		500	SPDT, 12A	5.25x 3.5x 1.48	x	x	
KTXW245SA6-x	Transmitter, Handheld, Watertight	1,2, 4 or 6		2.4	4	Factory Set	500		3.4x 2.6x 1.0			RCR245SA-6R
KTX245SA-12	Transmitter, Handheld	12		2.4	4	Factory Set	500		5.75 x 1.82 x 1.3			RCR245SA-6R
RCR245SA-6R	Receiver, Remote Control, Learning		6	2.4	4		500	SPDT, 12A	6.5x 3.85x 1.36	x	x	

Switch Followers, Remotes	Description	Buttons	Relays	Frequency (MHz)	Address Codes (Millions)	Address Selection2	Range ²	Relay Output ³	Size (Inches) ²	Input Channels	Hi-EMI Motor Noise Tolerant	Momentary, Latched & Toggle Modes	Use With
SF900-P	Switch Follower, Pair		4	902-928	8	Factory Set	1 Mile	SPDT, 12A	6.5x 3.85x 1.36	4	x	NA	This is a 2-unit set for Switch Follower applications
SF900	Switch Follower Transceiver		4	902-928	8	Factory Set	1 Mile	SPDT, 12A	6.5x 3.85x 1.36	4	x	x	SF900 or SFT900 depending on app
SFT900-x	Transmitter, Handheld Remote, Spread Spectrum	x=1, 2 or 4		902-928	8	Factory Set	1/2 Mile+		3.4x 2.6x 1.0			x	SF900

¹ Line-of-Sight, first number is with included whip antenna. Second number is with passive dipole antenna (DP Series Antennas). Longer range can be achieved with Active Dipole Antennas (DPA Series).
² Line-of-Sight with included rubber duck antenna. Higher gain antennas available.
³ 16-Amp Relays also available.

Optional Directional Antennas for use on Receivers

Model	Description	Frequency	Length
DP300A	Dipole Antenna w/7' Cable	303 MHz	11.15 in
DPA300A	Active Dipole Antenna w/7' Cable	303 MHz	19.90 in
DP400A	Dipole Antenna w/7' Cable	433 MHz	8.40 in
DPA400A	Active Dipole Antenna w/7' Cable	433 MHz	14.40 in
800253A-5	Whip, Swivel, 5dBi, RPSMA	2.4 GHz	7 in



NTX Series Remote Transmitter



KTX Series Keyfob Transmitter



Watertight Keyfob Transmitter



KTXW and SFT Series Handheld Transmitter



RCR Remote Receiver 3-Relays



RCR Remote Receiver 6-Relays



KTX245SA-12



SF Transceiver/Switch Follower 4-Relays